CS SERIES



A REAL PRODUCT, FOR THE REAL WORLD. The CS Series from ClipperCreek is designed to take the wear-and-tear of everyday use in all environments. Its tough NEMA 4 outdoor rated enclosure and rubber over-molded connector for the CS-60 and above ensures you can install this unit anywhere with confidence.

- MANY POWER LEVELS 16A to 80A charging
- QUALITY Technology that works for the life of your current plug-in vehicle and then some
- CONVENIENCE 25 feet of charging cable for installation and operation flexibility
- DURABILITY Rugged, fully sealed NEMA 4 enclosure for installation anywhere
- RELIABILITY- Backed by ClipperCreek's 1-year warranty, and outstanding customer service



CS SERIES PRODUCT OVERVIEW

ELECTRICAL SPECIFICATIONS

- Service 208V to 240V, 20A to 100A, single phase, 2 wire w/ground
- Charge Current or Output Power 208V to 240V, 16A to 80A continuous (3.8kW to 19.2kW)
- Service Ground Monitor Constantly checks for presence of proper safety ground
- Automatic Circuit Reclosure after minor power faults
- Charge Circuit Interruption Device Ground Fault Protection with fully automated self-test, eliminates manual user testing
- Cold Load Pickup Time-delayed and randomized to allow seamless re-energizing of unit following power outages
- External Control Input Allows external control from smart meter (AMI), billing or load management device

MATERIAL SPECIFICATIONS

- Indoor/outdoor rated fully sealed (NEMA 4) enclosure
- Operating Temperatures: -22°F to 122°F (-30°C to +50°C)
- 22" H x 17" W x 8" D (559mm H x 432mm W x 203mm D)
- Weight 33 lbs. (15kg) to 45lbs. (20.4kg)
- UL, cUL, ETL, cETL Listed

MULTIPLE CONFIGURATIONS

MODEL: I CS-100 CS-90 CS-80 CS-70 CS-60 CS-50 CS-40 CS-30 CIRCUIT BREAKER RATING: 100A 90A 80A 70A 60A 50A 40A 30A CONTINUOUS CURRENT: 80A 72A 64A 56A 48A 40A 32A 24A

CODES AND STANDARDS

- UL 2594 Electric Vehicle Supply Equipment
- **UL 2231** Personal Protection Device (i.e., CCID Hardware)
- UL 1998 Standard for Safety-Related Software
- UL 991 Standard for tests for Safety-Related Controls Employing Solid-State Devices
- NEC 625 Electric Vehicle Charge System
- SAE-J1772™ Electric Vehicle Conductive Charge Coupler



CS-20

20A

16A