

HCS SERIES



A REAL PRODUCT, FOR THE REAL WORLD. ClipperCreek's HCS charging stations come in a variety of power levels, as hardwired and plug-in units, and with multiple pedestal mount options. Recent additions to the HCS product line include the HCS-60R and HCS-80R, 'ruggedized' versions of our most powerful HCS models, offering up to 64 Amp charging; and the ChargeGuard®, a simple key-based access control option.

- **FAST CHARGING** - Up to 15.4kW of power to charge your vehicle quickly
- **QUALITY** - Technology that works for the life of your current plug-in vehicle and then some
- **CONVENIENT** - 25 feet of charging cable for installation flexibility and superior vehicle reach
- **DURABLE** - Rugged, fully sealed NEMA 4 enclosure for installation anywhere
- **RELIABLE** - Backed by ClipperCreek's exceptional warranty and outstanding customer service



HCS SERIES

PRODUCT OVERVIEW

CALL US TO ORDER TODAY!
585.533.4051
7464 W. HENRIETTA ROAD | RUSH, NY 14543

ELECTRICAL SPECIFICATIONS

- **Certifications** - ETL, cETL Listed
- **Service** - 208V to 240V - 20A to 80A, single phase, 2 wire w/ground
- **Charge Current Output Power** - 208V to 240V-16A to 64A continuous (3.3kW to 15.4kW)
- **Service Ground Monitor** - Constantly checks for presence of proper safety ground
- **Automatic Circuit Reclosure** - After minor power faults
- **Charge Circuit Interruption Device** - Ground fault protection with fully automated self-test, eliminates manual user testing

MATERIAL SPECIFICATIONS

- 25 foot charging cable
- Three year warranty
- Install hardwired or plug-in
- Indoor/outdoor rated fully sealed (NEMA 4) enclosure
- Operating temperatures: -22°F to 122°F (-30°C to 50°C)
- Wall mount holster included



ACCESS CONTROL OPTION AVAILABLE \$78 additional

ChargeGuard® Reliable key-based access control designed for fleet, workplace, multi-tenant, hospitality and residential charging.

MULTIPLE CONFIGURATIONS

MODEL:	HCS-20	HCS-30	HCS-40*	HCS-50*	HCS-60	HCS-80
CIRCUIT BREAKER RATING:	20A	30A	40A	50A	60A	80A
MAXIMUM CURRENT:	16A	24A	32A	40A	48A	64A



RUGGEDIZED OPTION AVAILABLE

HCS-40R, HCS-40PR, HCS-60R and HCS-80R

- 5-year warranty
- Impact and crush-resistant SAE-J1772™ connector
- Type 4X watertight and corrosion resistant rubber overmolded EV connector
- Available for plug-in installations with NEMA 14-50 or NEMA 6-50 plugs (HCS-40 only)



Share2® OPTION Maximize your Infrastructure Investment

- Turn one charging spot into two with HCS Share2®
- Full power charging for one vehicle, split power charging for two vehicles
- Compatible with ChargeGuard® enabled and Ruggedized HCS stations
- Power Sharing from a single circuit between two charging stations

