

JUICEBOX® 40

Residential Charging Stations



JuiceBox



Charge forward with the best-selling smart home charging station

JuiceBox 40, the best-selling smart home charging station, combines speed, performance and value. Enjoyed by thousands of satisfied EV drivers, it delivers all the safety and smart charging features you need to make home charging easy, reliable and cost-effective.

JuiceBox is the only line of charging stations that affords both direct user control and smart grid optimization, accessible through our software platform, JuiceNet®.

- Control charging anywhere, anytime via our mobile app and web portal
- Reduce your energy costs by scheduling charging when rates are low
- Select a cleaner electricity mix to reduce your emissions (in applicable geographies)
- Participate in smart grid programs to further lower the cost of owning and driving your EV (in applicable geographies)

Why JuiceBox?

Up to 7x Faster Charging

Spend less time waiting for your EV to charge and more time enjoying the drive

Powered by JuiceNet

Monitor and schedule charging with intuitive mobile app and web portal to save time and

Easy to Use and Install

for indoor/outdoor installation

Universal Compatibility

SAE-J1772™ plug ensures compatibility with all EVs*

Cleaner Driving

Optimize charging times and participate in smart grid programs to reduce emissions; **ENERGY STAR®-certified**

See Charger Status

Dynamic LED lights display WiFi connectivity and charging behavior

^{*}Tesla requires adapter

enel x

Luisa Pay® 40 Sacaifia	6.8"/17.3 cm
JuiceBox® 40 Specific	ations JuiceBox
Electrical Characteristics	 Safety Rated: 40A Max Single phase input: nominal voltage 208-240 VAC ~60 Hz Power: 8.3 kW at 208 VAC; 9.6 kW at 240 VAC
Input Cable & Plug	 2 ft/0.6 m with NEMA with 14-50 and 6-50 plug options. 2.5 ft/0.8 m hardwire pigtail
Output Cable & Connector	 25 ft/7.6 m cable J1772 standard compliant
EV JuiceNet® App	 > Precision measurement of power, energy, voltage & current > Automated notifications: time-of-use in effect, start of charge, end of charge, unit offline, unit back online, car not plugged in by a set time > Web-based portal for desktop access > See EV JuiceNet app data sheet for more on convenient features
Smart Grid Connectivity	> Built-in WiFi connectivity (802.11 b/g/n 2.4 GHz)
Firmware	 End-to-end AES-256-based encrypted protocols 90-day, 15-minute interval data storage Over-the-air (OTA) upgradeable firmware Persistent data storage upon power interruption
Emissions Reduction	Available via optional JuiceNet Green software upgrade
Enclosure	 Dynamic LED lights show charging status: network connectivity, charging in progress, delaying charging, standby, charge complete/EV not drawing power IP66: Weatherproof, dust-tight, polycarbonate enclosure IK10: Resistant polycarbonate case Quick-release wall mounting bracket included Built-in security lock and integrated cable management Operating Temperature: -40°F to 140°F (-40°C to 60°C)
Weight & Dimensions	 Main enclosure: H: 18.5 in/469 mm x W: 6.8 in/173 mm x D: 5.8 in/147 mm 15 lbs/6.8 kg
Codes & Standards	 FCC Part 15 Class B, NEC 625 compliant, ENERGY STAR® OpenADR 2.0b compliant
Safety	> UL and cUL Listed
Warranty	 3-year limited product warranty (parts only) for use under normal residential operating conditions
Made in North America	> From domestic & imported parts

CALL US TO ORDER TODAY!

585.533.4051

7464 W. HENRIETTA ROAD | RUSH, NY 14543

2020.11.02